

ISO/IEC JTC 1/SC 29/WG 04
MPEG Video Coding
Convenorship: CN

Document type:	Output Document
Title:	IV-PSNR 4.0 manual
Status:	Approved
Date of document:	2022-07-29
Source:	ISO/IEC JTC 1/SC 29/WG 04
Expected action:	None
Action due date:	None
No. of pages:	7 (without cover page)
Email of Convenor:	yul@zju.edu.cn
Committee URL:	https://sd.iso.org/documents/ui/#!/browse/iso/iso-iec-jtc-1/iso-iec-jtc-1-sc-29/iso-iec-jtc-1-sc-29-wg-4

**INTERNATIONAL ORGANIZATION FOR STANDARDIZATION
 ORGANISATION INTERNATIONALE DE NORMALISATION
 ISO/IEC JTC 1/SC 29/WG 04 MPEG VIDEO CODING**

ISO/IEC JTC 1/SC 29/WG 04 N 0244

July 2022, Online

Title	IV-PSNR 4.0 manual
Source	WG 04, MPEG Video Coding
Status	Approved
Editor	Adrian Dziembowski
Serial Number	21857

1. Introduction

IV-PSNR [Dziembo22] is a PSNR-based objective quality metric adapted for Immersive Video applications. Compared to PSNR, two major modifications were added: Corresponding Pixel Shift and Global Color Difference. Corresponding Pixel Shift eliminates the influence of a slight shift of objects' edges caused by reprojection errors. Global Color Difference reduces the influence of different color characteristics of different input views.

Version 4.0 introduces optional masked mode (cf. section 2.2), as well as several performance improvements. When masked mode is not used, output of IV-PSNR v4.0 is exactly the same, as for IV-PSNR v2.1.1 and higher.

Detailed description of the IV-PSNR metric can be found in [Dziembo22]. Below, the general and simplified idea of the IV-PSNR is presented.

IV-PSNR for YUV file is calculated as:

$$IVPSNR_{YUV} = \frac{\sum_{c=0}^2 IVPSNR(c) \cdot CCW(c)}{\sum_{c=0}^2 CCW(c)},$$

where $CCW(c)$ is the Color Component Weight for each color component c and $IVPSNR(c)$ is the IV-PSNR for that component:

$$IVPSNR(c) = 10 \cdot \log \left(\frac{MAX^2}{IVMSE(c)} \right),$$

where MAX is the maximum value of the color component (e.g. 1023 for 10-bit video) and:

$$IVMSE(c) = \frac{1}{W \cdot H} \sum_{y=0}^{H-1} \sum_{x=0}^{W-1} \min_{\substack{x_R \in [x-CPS, x+CPS] \\ y_R \in [y-CPS, y+CPS]}} (c_T(x, y, c) - c_R(x_R, y_R, c) + GCD(c))^2,$$

where W and H are width and height of the image, $c_T(x, y, c)$ and $c_R(x, y, c)$ are values of color component c in the position (x, y) in the test image and the reference image, respectively, CPS is the maximum Corresponding Pixel Shift between reference and test image, and GCD is the Global Color Difference for component c :

$$\text{GCD}(c) = \max\left(\frac{1}{W \cdot H} \sum_{y=0}^{H-1} \sum_{x=0}^{W-1} (c_R(x, y, c) - c_T(x, y, c)), \text{MUD}(c)\right),$$

where $\text{MUD}(c)$ is the Maximum Unnoticeable Difference for color component c .

In order to provide better quality assessment for omnidirectional video, WS-PSNR technique [Sun17] was applied (however, in the current version of the IV-PSNR software only the equirectangular projection is supported):

$$\text{WS-IVMSE}(c) = \frac{\sum_{y=0}^{H-1} \sum_{x=0}^{W-1} \min_{\substack{x_R \in [x-\text{CPS}, x+\text{CPS}] \\ y_R \in [y-\text{CPS}, y+\text{CPS]}} (c_T(x, y, c) - c_R(x_R, y_R, c) + \text{GCD}(c))^2 \cdot w_{x,y}}{\sum_{y=0}^{H-1} \sum_{x=0}^{W-1} w_{x,y}},$$

where weight $w_{x,y}$ is calculated as:

$$w_{x,y} = \cos \frac{\left(y + 0.5 - \frac{H}{2}\right) \cdot \pi}{H},$$

where x, y is a position of the pixel in ERP image and H is the height of this image.

$\text{CCW}(c)$, $\text{MUD}(c)$ and CPS values are predefined:

- $\text{CCW}(c)$:
 - $\text{CCW}(0) = 1$ (luma component),
 - $\text{CCW}(1) = 0.25$ (1st chroma component),
 - $\text{CCW}(2) = 0.25$ (2nd chroma component),
- $\text{MUD}(c) = 1\%$ for all the color components,
- $\text{CPS} = 2$.

IV-PSNR is calculated separately for each frame of the sequence. In the end, the mean IV-PSNR value is returned.

The IV-PSNR quality metric is based on PSNR, therefore, the higher the number, the better is the quality.

2. Software manual

IV-PSNR v4.0 accepts commandline parameters listed in section 2.1:


2.1 Commandline parameters

General parameters		
Cmd	ParamName	Description
-i0	InputFile0	YUV file path – reference
-i1	InputFile1	YUV file path – tested
-w	PictureWidth	Width of sequence
-h	PictureHeight	Height of sequence
-bd	BitDepth	Bit depth (optional, default: 8, up to 14)
-cf	ChromaFormat	Chroma format (optional, default: 420) [420, 444]
-s0	StartFrame0	Start frame (optional, default: 0)
-s1	StartFrame1	Start frame (optional, default: 0)
-l	NumberOfFrames	Number of frames to be processed (optional, default: -1 = all)
-o	OutputFile	Output file path (optional)
Equirectangular parameters		
Cmd	ParamName	Description
-erp	Equirectangular	Equirectangular sequence (flag, default disabled)
-lor	LonRangeDeg	Longitudinal range of ERP sequence [°] (optional, default: 360)
-lar	LatRangeDeg	Lateral range of ERP sequence [°] (optional, default: 180)
IV-PSNR specific parameters		
Cmd	ParamName	Description
-sr	SearchRange	IV-PSNR search range around center point (optional, default: 2 = 5×5)
-cws	ComponentWeights	IV-PSNR component weights ("Lm:Cb:Cr:0" – per component integer weight, default: "4:1:1:0", quotes required, requires USE_RUNTIME_CMPWEIGHTS = 1)
-unc	UnnoticeableCoef	IV-PSNR unnoticeable color difference threshold coeff ("Lm:Cb:Cr:0" – per component coeff, default: "0.01:0.01:0.01:0", quotes required)
WS-PSNR specific parameters		
Cmd	ParamName	Description
-ws8	Legacy8bitWSPSNR	Use 1020 as peak value for 10-bps videos in WSPSNR metric (provides compatibility with original WSPSNR implementation, optional, default: 1)
Application parameters		
Cmd	ParamName	Description
-t	NumberOfThreads	Number of worker threads if compiled with OpenMP (optional, default: -1 = all, suggested 4-8)
-ilp	InterleavedPic	Use additional image buffer with interleaved layout (improves performance at a cost of increased memory usage, optional, default: 1)
-v	VerboseLevel	Verbose level (optional, default: 2), cf. section 2.3
External config file		
Cmd	ParamName	Description
-c		Valid path to external config file – in INI format (optional), cf. section 2.5
Masked mode parameters		
Cmd	ParamName	Description
-im	InputFileM	YUV file path – mask (optional, same resolution as InputFile0 and InputFile1)
-bdm	BitDepthM	Bit depth for mask (optional, default: BitDepth, up to 16)
-cfm	ChromaFormatM	Chroma format for mask (optional, default: ChromaFormat) [400, 420, 444]

- The commandline parameters are position-intependent.
- When no parameters are used, syntax help is outputted.

2.2 Masked mode

Optional mode of the IV-PSNR 4.0 allows to calculate IV-PSNR value only for specified areas. In order to use masked mode, InputFileM (-im) parameter has to be set, indicating a path of mask YUV file.



In an example above, the IV-PSNR value is calculated only for occupied pixels (as indicated by mask), so different color of the unoccupied background does not impact outputted quality.

Requirements and notes

- Resolution of mask file has to be identical as input file.
- Allowed mask values are 0 (interpreted as inactive pixel) and $(1 \ll \text{BitDepthM}) - 1$ (interpreted as active pixel). Behavior for other values is undefined at this moment.
- The data processing functions for masked mode are not implemented with the use of SIMD instructions.

2.3 Verbose levels

Value	Printed data
0	final PSNR, WS-PSNR, IV-PSNR values only
1	0 + configuration + detected number of frames
2	1 + argc/argv + frame level PSNR, WS-PSNR, IV-PSNR
3	2 + computing time (LOAD, PSNR, WS-PSNR, IV-PSNR) (uses high resolution clock, could slightly slow down computations)
4	3 + IV-PSNR specific debug data (GlobalColorShift, R2T+T2R)

2.4 Compile-time parameters

Parameter name	Default value	Description
USE SIMD	1	use SIMD (to be precise... use SSE 4.1 or AVX2)
USE_KBNS	1	use Kahan-Babuška-Neumaier floating point summation algorithm (reduces accumulation errors)
USE_RUNTIME_CMPWEIGHTS	1	use component weights provided at runtime

2.5 Config file example

InputFile0	= "SA_ref.yuv"
InputFile1	= "SA_test.yuv"
PictureWidth	= 4096
PictureHeight	= 2048
BitDepth	= 10
ChromaFormat	= 420
VerboseLevel	= 3
OutputFile	= "IV-PSNR.txt"

2.6 Compilation requirements

The IVPSNR v4.0 software uses following external components:

- “Formatting library for C++” (libfmt) – distributed under BSD license and included in IVPSNR source package.

In order to build the software, the ISO C++17 conformant compiler is required.

3. Examples

1. IV-PSNR of SA_ref.yuv and SA_test.yuv. Sequence resolution is 4096×2048, YUV420, 10 bits per sample. Sequence format is ERP. Mean IV-PSNR calculated for the first 20 frames will be written into IV-PSNR.txt:

```
IV-PSNR -i0 SA_ref.yuv -i1 SA_test.yuv -w 4096 -h 2048 -bd 10 -erp -l 20 -o IV-PSNR.txt
```

2. IV-PSNR of SD_ref.yuv and SD_test.yuv. Sequence resolution is 2048×1088, YUV420, 8 bits per sample. Sequence format is perspective. Mean IV-PSNR calculated for all frames will be written into results.txt:

```
IV-PSNR -i0 SD_ref.yuv -i1 SD_test.yuv -o results.txt -w 2048 -h 1088
```

3. IV-PSNR of SC_ref.yuv and SC_test.yuv. Sequence resolution is 4096×2048, YUV420, 10 bits per sample. Sequence format is ERP, with lateral range equal to 90°. Mean IV-PSNR calculated for 5 frames (frames 0-4 of reference video and 10-14 of test video) will be written into o.txt:

```
IV-PSNR -i0 SC_ref.yuv -i1 SC_test.yuv -w 4096 -h 2048 -erp -lar 90 -l 5 -s1 10 -o o.txt
```

4. Using config file:

```
IV-PSNR -c "config.cfg"
```

5. Using external config file with some parameters added/overridden:

```
IV-PSNR -c "config.cfg" -v 1 -t 4
```

4. Software

MPEG Git Repository: <http://mpegx.int-evry.fr/software/MPEG/MIV/RS/IVPSNR>
Public read-only access: <https://gitlab.com/mpeg-i-visual/ivpsnr>
Software coordinator: Adrian Dziembowski, adrian.dziembowski@put.poznan.pl

5. Usage and citation

Please cite reference [Dziembo22] when using IV-PSNR.

6. References

- [Dziembo22] A. Dziembowski, D. Mieloch, J. Stankowski, and A. Grzelka, “IV-PSNR – the objective quality metric for immersive video applications,” IEEE Transactions on Circuits and Systems for Video Technology, 2022, DOI: [10.1109/TCSVT.2022.3179575](https://doi.org/10.1109/TCSVT.2022.3179575).
- [M48093] A. Dziembowski, M. Domański, “[MPEG-I Visual] Objective quality metric for immersive video,” ISO/IEC JTC1/SC29/WG11 MPEG/M48093, July 2019, Göteborg, Sweden.
- [M54279] J. Stankowski, A. Dziembowski, “[MPEG-I Visual] Fast implementation of IV-PSNR software,” ISO/IEC JTC1/SC29/WG11 MPEG/M54279, July 2020, Online.
- [M54896] J. Stankowski, A. Dziembowski, “Even faster implementation of IV-PSNR software,” ISO/IEC JTC1/SC29/WG04 MPEG VC/M54896, October 2020, Online.
- [M55752] A. Dziembowski, J. Stankowski, “Slightly faster IVPSNR,” ISO/IEC JTC1/SC29/WG04 MPEG VC/M55752, January 2021, Online.
- [M59974] J. Stankowski, A. Dziembowski, “[MIV] Improved IV-PSNR software,” ISO/IEC JTC1/SC29/WG04 MPEG VC/M59974, July 2022, Online.
- [Sun17] Y. Sun, A. Lu, L. Yu, “Weighted-to-Spherically-Uniform Quality Evaluation for Omnidirectional Video,” IEEE Signal Processing Letters 24.9(2017):1408-1412.

7. Changelog

v4.0 [M59974]:

- SIMD (SSE 4.1) implementation of IV-PSNR calculation (for interleaved picture buffers),
- wider SIMD (AVX2) implementation for most data processing functions,
- runtime adjustable component weights for IV-PSNR metric,
- adjustable search range for IV-PSNR metric,
- adjustable unnoticeable color difference threshold coeff for IV-PSNR metric,
- reading parameters from config file,
- protection against StartFrame >= DetectedFrames,
- writing error messages to stdout and stderr,
- non-performance critical parameters moved from compile-time to run-time selection,
- added mask file option.

v3.0 [M55752]:

- enabled INTERPROCEDURAL_OPTIMIZATION and assumed x86-64 Microarchitecture Feature Level >= x86-64-v2,
- new implementation picture I/O,
- reduced filesystem burden (avoid repetitive open-seek-read-close cycles),
- use of interleaved picture layout for IVPSNR calculation,
- SIMD (SSE 4.1) implementation for most data processing functions,
- dedicated thread pool instead of OpenMP directives (due to high OpenMP overhead).

v2.1.1 (no reference):

- bug fixes.

v2.1 [M54896]:

- support for parallel processing (using OpenMP),
- addition of PSNR and WS-PSNR [Sun17] values outputting,
- fixed WS-weight calculation for ERP sequences with non-180 lateral range,
- changed commandline arguments formatting,
- addition of detection of corrupted YUV files,
- change in compile-time parameters:
 - VERBOSE_LEVEL is now a commandline parameter,
 - WSPSNR_PEAK_VALUE_8BIT flag added (default: enabled), when enabled, the signal peak value is set to $255 \ll (\text{BitDepth} - 8)$. Otherwise, it is equal to $2^{\text{BitDepth} - 1}$.

v2.0 [M54279]:

- addition of (rOff) and (tOff) commandline parameters,
- removal of redundant GCD calculations,
- usage of uint16_t data type and 4:4:4 chroma format for internal picture storage,
- new implementation of pixel-level processing steps,
- reduction of filesystem burden by coalescing read,
- detection of read errors – causes application to exit returning EXIT_FAILURE,
- implementation of Kahanand-Babuska-Neumaier accumulation,
- improved conversion of 8bps input sequences,
- improved interpolation for input sequences with 4:2:0 chroma format,
- addition of 3 compile-time parameters:
 - VERBOSE_LEVEL – controls number of per-frame printing; default = 0,
 - USE_KBNS – enables the Kahan-Babuska-Neumaier accumulation; default: enabled,
 - USE_FIXED_WEIGHTS – enables faster 5×5 block search with fixed component weight (equal to 4:1:1); default = enabled,
- fixed possibility of reading from unallocated memory region during 5×5 block search,
- fixed GCD values rounding and clipping.

v1.0 [M48093].